

(12) United States Patent Hoeting et al.

(10) Patent No.:

US 6,543,284 B2

(45) Date of Patent:

Apr. 8, 2003

(54)	VESSEL WITH MEASURING CAPABILITY			
(75)	Inventors:	Michael G. Hoeting, Cincinnati, OH (US); Stephen C. Hoeting, Cincinnati, OH (US)		
(73)	Assignee:	WKI Holding Company, Inc., Reston, VA (US)		
(*)	Notice:	Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.		
		This patent is subject to a terminal dis-		

(21) Appl. No.: 09/908,529

Jul. 18, 2001 (22)Filed:

Prior Publication Data (65)US 2001/0042402 A1 Nov. 22, 2001

Related U.S. Application Data

(63)	Continuation-in-part of application No. 09/313,686, filed on
` ′	May 18, 1999, now Pat. No. 6,263,732.

	· ·		
(51)	Int. Cl. ⁷		G01F 19/00
(5-)	TIC CI	73/427; 33/1	V: D10/46 2
(52)	U.S. CI.	13/421, 33/1	v, D10/40.2

33/1 F, 522, 679.1; 215/365, 366; 222/23, 25, 26; D10/46.2

References Cited (56)

U.S. PATENT DOCUMENTS

153,159 A	7/1874	Dinwiddie	•••••	73/427
-----------	--------	-----------	-------	--------

216,530 A 423,018 A 1,507,968 A 1,564,470 A 1,722,101 A 2,165,045 A	3/1890 9/1924 12/1925 7/1929 7/1939	Pfitzenmeier Young Johnson Crimmel Little Garside	73/427 73/427 73/427 73/427 73/426
5,397,036 A		Maiwald	

Primary Examiner—Christopher W. Fulton (74) Attorney, Agent, or Firm-Seyfarth Shaw

ABSTRACT

A measuring vessel has cavity-defining wall structures and at least one ramp which rises from about the bottom of the wall structure toward the top of the wall structure. The at least one ramp has an upwardly directed surface with a lateral inner edge integral with portions of the wall structure below the ramp and a lateral outer edge integral with portions of the wall structure below the ramp. Indicia on the upwardly directed surface of the at least one ramp allows a user to look downwardly into the measuring vessel to visually detect the volume level of the contents in the vessel, thereby eliminating the need to look horizontally at the vessel at eye level. Preferably the vessel has two ramps, with at least one bearing indicia of standard English units, and another bearing indicia of metric units. In one embodiment a handle, covered with a cushioning grip sheath, is cantilevered from the top of the wall structure and has a distal end at the level of the bottom of the wall structure for cooperation therewith to support the vessel on an underlying support surface.

37 Claims, 3 Drawing Sheets

